

# BLP15M9S70

Power LDMOS transistor

Rev. 2 — 23 February 2021

AMPLEON

Product data sheet

## 1. Product profile

### 1.1 General description

A 70 W general purpose LDMOS RF power transistor for broadcast and ISM applications in HF to 2 GHz band.

Table 1. Application performance

| Test signal | f     | P <sub>L</sub> | G <sub>p</sub> | η <sub>D</sub> | RL <sub>in</sub> |
|-------------|-------|----------------|----------------|----------------|------------------|
|             | (MHz) | (W)            | (dB)           | (%)            | (dB)             |
| pulsed CW   | 1400  | 70             | 17.6           | 70             | −14              |
| CW          | 915   | 70             | 17             | 75             | −17              |

### 1.2 Features and benefits



- High efficiency
- Integrated dual sided ESD protection
- Excellent ruggedness
- High power gain
- Excellent reliability
- Easy power control
- For RoHS compliance see the product details on the Ampleon website

### 1.3 Applications

- RF power amplifiers for CW applications
- Industrial, scientific and medical applications
- Broadcast transmitter applications

## 2. Pinning information

Table 2. Pinning

| Pin | Description | Simplified outline  | Graphic symbol  |
|-----|-------------|---|---|
| 1   | drain       |  |  |
| 2   | gate        |   |   |
| 3   | source      |   |   |

[1] Connected to flange.

## 3. Ordering information

Table 3. Ordering information

| Package name | Orderable part number | 12NC           | Packing description             | Min. orderable quantity (pieces) |
|--------------|-----------------------|----------------|---------------------------------|----------------------------------|
| SOT1482-1    | BLP15M9S70Z           | 9349 602 43515 | TR13; 500-fold; 24 mm; dry pack | 500                              |

## 4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol    | Parameter            | Conditions | Min | Max  | Unit |
|-----------|----------------------|------------|-----|------|------|
| $V_{DS}$  | drain-source voltage |            | -   | 65   | V    |
| $V_{GS}$  | gate-source voltage  |            | -6  | +13  | V    |
| $T_{stg}$ | storage temperature  |            | -65 | +150 | °C   |
| $T_j$     | junction temperature | [1]        | -   | 225  | °C   |

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

## 5. Thermal characteristics

Table 5. Thermal characteristics

| Symbol        | Parameter                                | Conditions  | Typ  | Unit |
|---------------|--|---|------|------|
| $R_{th(j-c)}$ | thermal resistance from junction to case | $T_{case} = 85\text{ °C}$ ; $V_{DS} = 32\text{ V}$ ;<br>$P_L = 70\text{ W}$ | 1.44 | K/W  |

## 6. Characteristics

**Table 6. DC characteristics**

$T_j = 25\text{ }^{\circ}\text{C}$ ; unless otherwise specified.

| Symbol        | Parameter                        | Conditions  | Min | Typ  | Max | Unit             |
|---------------|----------------------------------|---|-----|------|-----|------------------|
| $V_{(BR)DSS}$ | drain-source breakdown voltage   | $V_{GS} = 0\text{ V}$ ; $I_D = 0.66\text{ mA}$                    | 65  | 70   | -   | V                |
| $V_{GS(th)}$  | gate-source threshold voltage    | $V_{DS} = 10\text{ V}$ ; $I_D = 66\text{ mA}$                     | 1.5 | 2.0  | 2.5 | V                |
| $I_{DSS}$     | drain leakage current            | $V_{GS} = 0\text{ V}$ ; $V_{DS} = 32\text{ V}$                    | -   | -    | 1.4 | $\mu\text{A}$    |
| $I_{DSX}$     | drain cut-off current            | $V_{GS} = V_{GS(th)} + 3.75\text{ V}$ ;<br>$V_{DS} = 10\text{ V}$ | -   | 12.6 | -   | A                |
| $I_{GSS}$     | gate leakage current             | $V_{GS} = 11\text{ V}$ ; $V_{DS} = 0\text{ V}$                    | -   | -    | 140 | nA               |
| $R_{DS(on)}$  | drain-source on-state resistance | $V_{GS} = V_{GS(th)} + 3.75\text{ V}$ ;<br>$I_D = 2.31\text{ A}$  | -   | 185  | -   | $\text{m}\Omega$ |

**Table 7. AC characteristics**

$T_j = 25\text{ }^{\circ}\text{C}$ ; unless otherwise specified.

| Symbol    | Parameter                    | Conditions  | Min | Typ  | Max | Unit |
|-----------|------------------------------|---|-----|------|-----|------|
| $C_{iss}$ | input capacitance            | $V_{GS} = 0\text{ V}$ ; $V_{DS} = 50\text{ V}$ ; $f = 1\text{ MHz}$ | -   | 61   | -   | pF   |
| $C_{oss}$ | output capacitance           | $V_{GS} = 0\text{ V}$ ; $V_{DS} = 50\text{ V}$ ; $f = 1\text{ MHz}$ | -   | 22   | -   | pF   |
| $C_{rss}$ | reverse transfer capacitance | $V_{GS} = 0\text{ V}$ ; $V_{DS} = 50\text{ V}$ ; $f = 1\text{ MHz}$ | -   | 0.45 | -   | pF   |

**Table 8. RF characteristics**

RF characteristics in Ampleon production test circuit; typical RF performance at  $T_{case} = 25\text{ }^{\circ}\text{C}$ ;  
 $V_{DS} = 32\text{ V}$ ;  $I_{DQ} = 300\text{ mA}$ ;  $t_p = 100\text{ }\mu\text{s}$ ;  $\delta = 10\text{ }\%$ .


| Symbol                     | Parameter         | Conditions                                  | Min  | Typ  | Max | Unit |
|----------------------------|-------------------|---|------|------|-----|------|
| <b>Pulsed RF, class-AB</b> |                   |   |      |      |     |      |
| $G_p$                      | power gain        | $f = 1400\text{ MHz}$ ; $P_L = 70\text{ W}$ | 16.5 | 17.8 | -   | dB   |
| $\eta_D$                   | drain efficiency  | $f = 1400\text{ MHz}$ ; $P_L = 70\text{ W}$ | 61   | 65.5 | -   | %    |
| $RL_{in}$                  | input return loss | $f = 1400\text{ MHz}$ ; $P_L = 70\text{ W}$ | -    | -17  | -   | dB   |

## 7. Test information

### 7.1 Ruggedness in class-AB operation

The BLP15M9S70 is capable of withstanding a load mismatch corresponding to a  $VSWR = 10 : 1$  through all phases under the following conditions:  $V_{DS} = 32\text{ V}$ ;  
 $f = 1400\text{ MHz}$  at rated load power on RF development board using a pulsed CW RF signal which has  $\sim 150\text{ ns}$  rise and fall time.

## 7.2 Test circuit




**Table 9. List of components**

See [Figure 1](#) for component layout.

| Component                 | Description                       | Value                    | Remarks                |
|---------------------------|-----------------------------------|--------------------------|------------------------|
| C1, C2                    | multilayer ceramic chip capacitor | 6.2 pF                   | ATC 800A               |
| C3                        | multilayer ceramic chip capacitor | 2 pF                     | ATC 800A               |
| C5, C6, C9, C17, C19, C16 | multilayer ceramic chip capacitor | 100 pF                   | ATC 800A               |
| C8, C11, C18, C20         | multilayer ceramic chip capacitor | 100 nF, 100 V            |                        |
| C12, C13                  | multilayer ceramic chip capacitor | 3 pF                     | ATC 800A               |
| C14, C15                  | multilayer ceramic chip capacitor | 2.1 pF                   | ATC 800A               |
| C21                       | electrolytic capacitor            | 220 $\mu\text{F}$ , 63 V |                        |
| R1, R2                    | chip resistor                     | 10 $\Omega$              | SMD 0805               |
| R3                        | shunt resistor                    | 10 m $\Omega$            | for current monitoring |


### 7.3 Graphical data



$V_{DS} = 32 \text{ V}$ ;  $f = 1400 \text{ MHz}$ ;  $t_p = 100 \text{ } \mu\text{s}$ ;  $\delta = 10 \text{ } \%$ .

- (1)  $I_{Dq} = 200 \text{ mA}$
- (2)  $I_{Dq} = 250 \text{ mA}$
- (3)  $I_{Dq} = 300 \text{ mA}$
- (4)  $I_{Dq} = 400 \text{ mA}$


**Fig 2. Power gain as a function of output power; typical values**



$V_{DS} = 32 \text{ V}$ ;  $f = 1400 \text{ MHz}$ ;  $t_p = 100 \text{ } \mu\text{s}$ ;  $\delta = 10 \text{ } \%$ .


- (1)  $I_{Dq} = 200 \text{ mA}$
- (2)  $I_{Dq} = 250 \text{ mA}$
- (3)  $I_{Dq} = 300 \text{ mA}$
- (4)  $I_{Dq} = 400 \text{ mA}$

**Fig 3. Drain efficiency as a function of output power; typical values**



$V_{DS} = 32 \text{ V}$ ;  $I_{Dq} = 300 \text{ mA}$ ;  $f = 1400 \text{ MHz}$ ;  $t_p = 100 \text{ } \mu\text{s}$ ;  $\delta = 10 \text{ } \%$ .


**Fig 4. Power gain and drain efficiency as function of peak output power; typical values**



$I_{Dq} = 300 \text{ mA}$ ;  $f = 1400 \text{ MHz}$ ;  $t_p = 100 \text{ } \mu\text{s}$ ;  $\delta = 10 \text{ } \%$ .

- (1)  $V_{DS} = 32 \text{ V}$
- (2)  $V_{DS} = 30 \text{ V}$
- (3)  $V_{DS} = 28 \text{ V}$

**Fig 5. Power gain as a function of output power; typical values**



$I_{DQ} = 300$  mA;  $f = 1400$  MHz;  $t_p = 100$   $\mu$ s;  $\delta = 10$  %.

(1)  $V_{DS} = 32$  V

(2)  $V_{DS} = 30$  V

(3)  $V_{DS} = 28$  V

**Fig 6. Drain efficiency as a function of output power; typical values**

8. Package outline





Fig 7. Package outline SOT1482-1 (sheet 1 of 2)

SOT1482-1

| Drawing Notes |   |
|---------------|---|
| Items         | Description   |
| (1)           | Dimensions are excluding mold protrusion. The mold protrusion is maximum 0.15 mm per side. See also detail B.<br>In the dambar area max. protrusion is 0.55 mm. max. in length and 0.3 mm. max. in width (4x). See also detail B. |
| (2)           | The lead dambar (metal) protrusions are not included. Add 0.14 mm max to the total lead dimension at the dambar location.   |
| (3)           | The leads and exposed heatsink are plated with matte Tin (Sn).  |
| (4)           | Dimensions (Heatsink ears) 10,67 and 1,78 do not include mouldprotrusion. Overall Max. dimensions incl. mould protrusions is 10.92 mm. (max.) and 2.03 mm. (max.)   |
| (5)           | Lead coplanarity over the leads is 0,1 mm. maximum.   |
| (6)           | Surfaces may remain unplated (not solderable surfaces)  |
|               |   |




|                          |              |  |  |
|--------------------------|--------------|--|--|
| Package outline drawing: | units in mm. | Tolerances unless otherwise stated:<br>Dimension: $\pm 0.05$ Angle: $\pm 1^\circ$                          | Revision: 6<br>Revision date: 1/4/2017 |
| SOT1482-1                |              |  Third angle projection | Sheet 2 of 2                           |

Fig 8. Package outline SOT1482-1 (sheet 2 of 2)



## 9. Handling information

### CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

**Table 10. ESD sensitivity**

| ESD model  | Class                   |
|--|-------------------------|
| Charged Device Model (CDM); According to ANSI/ESDA/JEDEC standard JS-002 | C2A <a href="#">[1]</a> |
| Human Body Model (HBM); According to ANSI/ESDA/JEDEC standard JS-001     | 2 <a href="#">[2]</a>   |

[1] CDM classification C2A is granted to any part that passes after exposure to an ESD pulse of 500 V.

[2] HBM classification 2 is granted to any part that passes after exposure to an ESD pulse of 2000 V.

## 10. Abbreviations

**Table 11. Abbreviations**

| Acronym | Description                                  |
|---------|--|
| CW      | Continuous Wave                              |
| ESD     | ElectroStatic Discharge                      |
| ISM     | Industrial, Scientific and Medical           |
| LDMOS   | Laterally Diffused Metal-Oxide Semiconductor |
| MTF     | Median Time to Failure                       |
| RoHS    | Restriction of Hazardous Substances          |
| SMD     | Surface Mounted Device                       |
| VSWR    | Voltage Standing Wave Ratio                  |

## 11. Revision history

**Table 12. Revision history**

| Document ID    | Release date   | Data sheet status  | Change notice | Supersedes     |
|----------------|--|--------------------|---------------|----------------|
| BLP15M9S70 v.2 | 20210223   | Product data sheet | -             | BLP15M9S70 v.1 |
| Modifications: | <ul style="list-style-type: none"> <li><a href="#">Section 1.1 on page 1</a>: updated description first paragraph</li> <li><a href="#">Table 1 on page 1</a>: updated table</li> <li><a href="#">Section 1.3 on page 1</a>: changed first list item</li> <li><a href="#">Table 6 on page 3</a>: updated table</li> <li><a href="#">Table 8 on page 3</a>: updated table</li> </ul> |                    |               |                |
| BLP15M9S70 v.1 | 20200807   | Product data sheet | -             | -              |

## 12. Legal information

### 12.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

### 12.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 12.3 Disclaimers

**Maturity** — The information in this document can only be regarded as final once the relevant product(s) has passed the Release Gate in Ampleon's release process. Prior to such release this document should be regarded as a draft version.

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

**Right to make changes** — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon's warranty of the product for such

automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon's standard warranty and Ampleon's product specifications.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

## 12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 13. Contact information

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

## 14. Contents

---

|           |  |           |
|-----------|--|-----------|
| <b>1</b>  | <b>Product profile</b> .....           | <b>1</b>  |
| 1.1       | General description .....              | 1         |
| 1.2       | Features and benefits .....            | 1         |
| 1.3       | Applications .....                     | 1         |
| <b>2</b>  | <b>Pinning information</b> .....       | <b>2</b>  |
| <b>3</b>  | <b>Ordering information</b> .....      | <b>2</b>  |
| <b>4</b>  | <b>Limiting values</b> .....           | <b>2</b>  |
| <b>5</b>  | <b>Thermal characteristics</b> .....   | <b>2</b>  |
| <b>6</b>  | <b>Characteristics</b> .....           | <b>3</b>  |
| <b>7</b>  | <b>Test information</b> .....          | <b>3</b>  |
| 7.1       | Ruggedness in class-AB operation ..... | 3         |
| 7.2       | Test circuit. ....                     | 4         |
| 7.3       | Graphical data .....                   | 5         |
| <b>8</b>  | <b>Package outline</b> .....           | <b>7</b>  |
| <b>9</b>  | <b>Handling information</b> .....      | <b>9</b>  |
| <b>10</b> | <b>Abbreviations</b> .....             | <b>9</b>  |
| <b>11</b> | <b>Revision history</b> .....          | <b>9</b>  |
| <b>12</b> | <b>Legal information</b> .....         | <b>10</b> |
| 12.1      | Data sheet status .....                | 10        |
| 12.2      | Definitions .....                      | 10        |
| 12.3      | Disclaimers .....                      | 10        |
| 12.4      | Trademarks .....                       | 11        |
| <b>13</b> | <b>Contact information</b> .....       | <b>11</b> |
| <b>14</b> | <b>Contents</b> .....                  | <b>12</b> |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2021.

All rights reserved.

For more information, please visit: <http://www.ampleon.com>

For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 23 February 2021

Document identifier: BLP15M9S70