

**LOCOSYS**


GNSS Wireless & Communication



**Standard Modules**














































































**Sub-meter(L1+L5)**

**<1m (CEP)**

GPS Modules		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>												
 MC-1010-2RE		●	●					○	2.5m (CEP)	UART	① ② ④	10.1 x 9.7 x 2.0
MC-1513-2RE		●	●					○	3m (2D RMS)	UART	① ② ④	15.0 x 13.0 x 2.2
MC-1612-2RE		●	●					○	3m (2D RMS)	UART	① ② ④	16.0 x 12.2 x 2.2
MC-1010		●	●					○	2.5m (CEP)	UART	① ② ④	10.1 x 9.7 x 2.0
MC-1513		●	●					○	3m (2D RMS)	UART/I <sup>2</sup> C	① ② ④	15.0 x 13.0 x 2.2
MC-1612		●	●					○	3m (2D RMS)	UART	① ② ④	16.0 x 12.2 x 2.2
<b>HED</b>												
HD-1010		●	●					○	2.5m (CEP)	UART	① ② ③ ④	10.1 x 9.7 x 2.2
HD-1612		●	●					○	2.5m (CEP)	UART	① ② ③ ④	16.0 x 12.2 x 2.2



※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing





※  : Hot selling

GNSS Modules		GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>												
 MC-1010-G	   							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	10.1 x 9.7 x 2.0	
MC-1010-B	  							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	10.1 x 9.7 x 2.0	
MC-1513-G	   							1.2m (CEP)	UART/I <sup>2</sup> C	<b>1</b> <b>2</b> <b>4</b>	15.0 x 13.0 x 2.2	
MC-1513-B	  							2.5m (CEP)	UART/I <sup>2</sup> C	<b>1</b> <b>2</b> <b>4</b>	15.0 x 13.0 x 2.2	
 MC-1612-G	   							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b> <b>5</b>	16.0 x 12.2 x 2.2	
MC-1612-B	  							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b> <b>5</b>	16.0 x 12.2 x 2.2	
MC-1612-G2	   							1.2m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b> <b>5</b>	16.0 x 12.2 x 2.2	
MC-1612-B2	  							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b> <b>5</b>	16.0 x 12.2 x 2.2	
MC-1722-G	   							2.5m(CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	17.0 x 22.4 x 2.2	
MC-1722-B	  							2.5m(CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	17.0 x 22.4 x 2.2	
<b>STMicro</b>												
ST-1612i-G	   							1.8m(CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	16.0 x 12.2 x 2.4	
ST-1612i-B	  							1.8m(CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	16.0 x 12.2 x 2.4	
<b>HED</b>												
HD-1010-GA	   							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	10.1 x 9.7 x 2.2	
HD-1010-BA	  							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	10.1 x 9.7 x 2.2	
HD-1612-BA	  							2.5m (CEP)	UART	<b>1</b> <b>2</b> <b>4</b>	16.0 x 12.2 x 2.2	

※ Application : **1** HandHeld **2** Automotive **3** Drone **4** Marine **5** Timing

※  : Hot selling

Sub-meter Modules		GP	QZSS	GA	GL	BD	IR	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b> +1.8V													
 MC-1010-V2a	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART/I <sup>2</sup> C	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	10.1 x 9.7 x 2.2
 MC-1010-V3a	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART/I <sup>2</sup> C	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	10.1 x 9.7 x 2.2

Sub-meter Modules		GP	QZSS	GA	GL	BD	IR	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b> +3.3V													
 MC-1010-V2b	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	10.1 x 9.7 x 2.2
 MC-1010-V3b	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	10.1 x 9.7 x 2.2
 MC-1612-V2b	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	16.0 x 12.2x 2.4
 MC-1612-V3b	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	16.0 x 12.2x 2.4

<b>HED</b> +3.3V													
HD-1612-BV1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	16.0 x 12.2x 2.4
HD-1612-BV2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	16.0 x 12.2x 2.4
HD-1612-BV3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>		1.5m (CEP)	UART	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>	16.0 x 12.2x 2.4

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling





**LOCOSYS**

GNSS Wireless & Communication

# Smart Antenna Sub-Meter Antenna



## GPS Smart Antenna

	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>											
 LS2003C	●	●				○		3m (2D RMS)	UART	① ② ④	15.5 x 15.5 x 6.6
 LS2003C-2RE	●	●					○	3m (2D RMS)	UART	① ② ④	15.5 x 15.5 x 6.6
LS2003D	●	●				○		3m (2D RMS)	UART	① ② ④	21.0 x 17.0 x 7.2
LS2003D-2RE	●	●					○	3m (2D RMS)	UART	① ② ④	21.0 x 17.0 x 7.2
LS2003E	●	●				○		1.2m (CEP)	UART	① ② ④	22.0 x 22.0 x 8.4
LS2003E-2RE	●	●					○	1.2m (CEP)	UART	① ② ④	22.0 x 22.0 x 8.4
LS2003J-2RE	●	●					○	3m (2D RMS)	UART	① ② ④	16.0 x 12.2 x 2.8
 LS20030	●	●				○		3m(2D RMS)	USB	① ② ④	30.0 x 30.0 x 8.0
 LS20031	●	●				○		3m(2D RMS)	TTL	① ② ④	30.0 x 30.0 x 8.0
LS20032	●	●				○		3m(2D RMS)	RS232	① ② ④	30.0 x 30.0 x 8.0
LS20030-2RE	●	●					○	3m(2D RMS)	USB	① ② ④	30.0 x 30.0 x 8.0
LS20031-2RE	●	●					○	3m(2D RMS)	TTL	① ② ④	30.0 x 30.0 x 8.0
LS20032-2RE	●	●					○	3m(2D RMS)	RS232	① ② ④	30.0 x 30.0 x 8.0
<b>HED</b>											
LS2008E	●	●				○		2.5m (CEP)	UART	① ② ④	22.0 x 22.0 x 7.5




※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

## GNSS Smart Antenna

GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
----	------	----	----	----	-------	-----	-------------------	-----------	-------------	---------------

### MTK

LS2003J-G	●	●	●	●	○		2.5m (CEP)	UART	① ② ④	16.0 x 12.2 x 2.8
 LS2003C-G	●	●	●	●	○		1.2m (CEP)	UART	① ② ④	15.5 x 15.5 x 6.0
LS2003D-G	●	●	●	●	○		1.2m (CEP)	UART	① ② ④	15.5 x 15.5 x 6.0
LS2003E-G	●	●	●	●	○		1.2m (CEP)	UART	① ② ④	22.0 x 22.0 x 8.4
LS2003G-G-T	●	●	●	●	○		2.5 m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS2003G-G-R	●	●	●	●	○		2.5 m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0
LS2003G-G2-T	●	●	●	●	○		2.5 m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
 LS2003G-G2-R	●	●	●	●	○		2.5 m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS2003G-B2-T	●	●	●		●	○	2.5 m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS2003G-B2-R	●	●	●		●	○	2.5 m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
 LS20030-G	●	●	●	●	○		2.5m (CEP)	USB	① ② ③ ④	30.0 x 30.0 x 8.0
LS20031-G	●	●	●	●	○		2.5m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS20032-G	●	●	●	●	○		2.5m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

## GNSS Smart Antenna






	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>											
LS20030-B	●	●	●		●	○		2.5m (CEP)	USB	① ② ③ ④	30.0 x 30.0 x 8.0
LS20031-B	●	●	●		●	○		2.5m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS20032-B	●	●	●		●	○		2.5m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0
LS20030U-G	●	●	●	●		○		2.5m (CEP)	USB	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20031U-G	●	●	●	●		○		2.5m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20032U-G	●	●	●	●		○		2.5m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20030U-B	●	●	●		●	○		2.5m (CEP)	USB	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20031U-B	●	●	●		●	○		2.5m (CEP)	TTL	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
LS20032U-B	●	●	●		●	○		2.5m (CEP)	RS232	① ② ③ ④ ⑤	30.0 x 30.0 x 8.0
<b>HED</b>											
LS2008E-G	●	●	●	●	●	○		< 2.5m (CEP)	UART	① ② ④	22.0 x 22.0 x 7.5
<b>STMicro</b>											
LS2009G-G-T	●	●	●	●		○		< 1.6m (CEP)	TTL	① ② ③ ④	30.0 x 30.0 x 8.0
LS2009G-G-R	●	●	●	●		○		< 1.6m (CEP)	RS232	① ② ③ ④	30.0 x 30.0 x 8.0

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling



## Sub-meter Smart Antenna

	GP	QZSS	GA	GL	BD	IR	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>												
 LS2003H-V2	●	●	●	●	●		○		1.5 m (CEP)	UART / USB	① ②	14.0 x 9.6 x 2.0
 LS20030-V2	●	●	●	●	●		○		1.5 m (CEP)	USB	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20031-V2	●	●	●	●	●		○		1.5 m (CEP)	TTL	① ② ④ ⑤	30.0 x 30.0 x 8.0
 LS20032-V2	●	●	●	●	●		○		1.5 m (CEP)	RS232	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS2003H-V3	●	●	●	●	●	●	○		2.5 m (CEP)	UART / USB	① ②	14.0 x 9.6 x 2.0
 LS20030-V3	●	●	●	●	●	●	○		1.5 m (CEP)	USB	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20031-V3	●	●	●	●	●	●	○		1.5 m (CEP)	TTL	① ② ④ ⑤	30.0 x 30.0 x 8.0
 LS20032-V3	●	●	●	●	●	●	○		1.5 m (CEP)	RS232	① ② ④ ⑤	30.0 x 30.0 x 8.0
<b>HED</b>												
LS20080-BV2	●	●	●	●	●		○		1.5 m (CEP)	USB	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20081-BV2	●	●	●	●	●		○		1.5 m (CEP)	TTL	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20082-BV2	●	●	●	●	●		○		1.5 m (CEP)	RS232	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20080-BV3	●	●	●		●	●	○		1.5 m (CEP)	USB	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20081-BV3	●	●	●		●	●	○		1.5 m (CEP)	TTL	① ② ④ ⑤	30.0 x 30.0 x 8.0
LS20082-BV3	●	●	●		●	●	○		1.5 m (CEP)	RS232	① ② ④ ⑤	30.0 x 30.0 x 8.0

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

**LOCOSYS**

*GNSS Wireless & Communication*



**GNSS Mouse**

## GPS Mouse

GP QZSS GA GL BD

Position Accuracy

Interface

Connector

Application

Dimension(mm)

MTK



LS23030



2.5m

USB

USB

② ③ ④

49.0 x 41.0 x 14.1

LS23032



2.5m

RS232

PS2

② ③ ④

49.0 x 41.0 x 14.1

LS23033



2.5m

RS232

RJ11

② ③ ④

49.0 x 41.0 x 14.1



LS23035



2.5m

RS232

PS2

② ③ ④

49.0 x 41.0 x 14.1



LS23036



2.5m

RS232

RJ11

② ③ ④

49.0 x 41.0 x 14.1

LS23030-2RE



2.5m

USB

USB

② ③ ④

49.0 x 41.0 x 14.1

LS23032-2RE



2.5m

RS232

PS2

② ③ ④

49.0 x 41.0 x 14.1

LS23033-2RE



2.5m

RS232

RJ11

② ③ ④

49.0 x 41.0 x 14.1

LS23035-2RE



2.5m

RS232

PS21

② ③ ④

49.0 x 41.0 x 14.1

LS23036-2RE



2.5m

RS232




RJ11

② ③ ④

49.0 x 41.0 x 14.1

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※ : Hot selling

GNSS Mouse		GP	QZSS	GA	GL	BD	Position Accuracy	Interface	Connector	Application			Dimension(mm)
<b>MTK</b>													
 LS23030-G		●	●	●	●		2.5m	USB	USB	②	④		49.0 x 41.0 x 14.1
LS23032-G		●	●	●	●		2.5m	RS232	PS2	②	④		49.0 x 41.0 x 14.1
LS23033-G		●	●	●	●		2.5m	RS232	RJ11	②	④		49.0 x 41.0 x 14.1
 LS23035-G		●	●	●	●		2.5m	RS232	PS2	②	④		49.0 x 41.0 x 14.1
 LS23036-G		●	●	●	●		2.5m	RS232	RJ11	②	④		49.0 x 41.0 x 14.1
<b>STMicro</b>													
LS23092-G		●	●	●	●		1.6m	RS232	PS2	① ②	④		49.0 x 41.0 x 14.1
LS23093-G		●	●	●	●		1.6m	RS232	RJ11	① ②	④		49.0 x 41.0 x 14.1
LS23095-G		●	●	●	●		1.6m	RS232	PS2	① ②	④		49.0 x 41.0 x 14.1
LS23096-G		●	●	●	●		1.6m	RS232	RJ11	① ②	④		49.0 x 41.0 x 14.1
LS23092-G2		●	●	●	●		1.6m	RS232	PS2	① ②	④		49.0 x 41.0 x 14.1
LS23093-G2		●	●	●	●		1.6m	RS232	RJ11	① ②	④		49.0 x 41.0 x 14.1
LS23095-G2		●	●	●	●		1.6m	RS232	PS2	① ②	④		49.0 x 41.0 x 14.1
LS23096-G2		●	●	●	●		1.6m	RS232	RJ11	① ②	④		49.0 x 41.0 x 14.1

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

## Dead Reckoning Mouse

GP QZSS GA GL BD

Position Accuracy

Interface

Connector

Application

Dimension(mm)

MTK

LS23030-UDG



2.5m (CEP)  
5% (UDR)

USB

USB

② ③

49.0 x 41.0 x 14.1

LS23032-UDG



2.5m (CEP)  
5% (UDR)

RS232

PS2

② ③

49.0 x 41.0 x 14.1

 LS23035-UDG



2.5m (CEP)  
5% (UDR)

RS232

PS2

② ③

49.0 x 41.0 x 14.1

LS23036-UDG



2.5m (CEP)  
5% (UDR)

RS232

RJ11

② ③

49.0 x 41.0 x 14.1

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

**LOCOSYS**

GNSS Wireless & Communication


# Dead Reckoning Technology





## Dead Reckoning Modules

GP QZSS GA GL BD Flash ROM Position Accuracy Dead Reckoning P/R/Y Interface Application Dimension(mm)

### MTK

 MC-1612-DG (ADR/UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>	<span style="color:green">●</span>		<input type="radio"/>		2.5m (CEP) 0.5% (ADR) 5% (UDR)	<input type="radio"/>	<input type="radio"/>	UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">1</span> <span style="border:1px solid black; border-radius:50%; padding:2px;">2</span> <span style="border:1px solid black; border-radius:50%; padding:2px;">3</span>	16.0 x 12.2 x 2.4
MC-1612-DB (ADR/UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>		<span style="color:magenta">●</span>	<input type="radio"/>		2.5m (CEP) 0.5% (ADR) 5% (UDR)	<input type="radio"/>	<input type="radio"/>	UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">1</span> <span style="border:1px solid black; border-radius:50%; padding:2px;">2</span> <span style="border:1px solid black; border-radius:50%; padding:2px;">3</span>	16.0 x 12.2 x 2.4

### STMicro

 ST-1612i-DGO (ADR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>	<span style="color:green">●</span>		<input type="radio"/>		1.8m (CEP) 0.5% (ADR)	<input type="radio"/>		ODO	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612i-DGU (UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>	<span style="color:green">●</span>		<input type="radio"/>		1.8m (CEP) 5% (UDR)	<input type="radio"/>		UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612i-DBO (ADR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>		<span style="color:magenta">●</span>	<input type="radio"/>		1.8m (CEP) 0.5% (ADR)	<input type="radio"/>		ODO	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612i-DBU (UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>		<span style="color:magenta">●</span>	<input type="radio"/>		1.8m (CEP) 5% (UDR)	<input type="radio"/>		UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
 ST-1612r-DGO (ADR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>	<span style="color:green">●</span>		<input type="radio"/>		1.8m (CEP) 0.5% (ADR)	<input type="radio"/>	<input type="radio"/>	ODO	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612r-DGU (UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>	<span style="color:green">●</span>		<input type="radio"/>		1.8m (CEP) 5% (UDR)	<input type="radio"/>	<input type="radio"/>	UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612r-DBO (ADR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>		<span style="color:magenta">●</span>	<input type="radio"/>		1.8m (CEP) 0.5% (ADR)	<input type="radio"/>	<input type="radio"/>	ODO	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3
ST-1612r-DBU (UDR)	<span style="color:blue">●</span>	<span style="color:purple">●</span>	<span style="color:orange">●</span>		<span style="color:magenta">●</span>	<input type="radio"/>		1.8m (CEP) 5% (UDR)	<input type="radio"/>	<input type="radio"/>	UART	<span style="border:1px solid black; border-radius:50%; padding:2px;">2</span>	16.0 x 12.2 x 2.3

※ ADR /UDR : Automotive Dead Reckoning/ Untethered Dead Reckoning

※ P/ R/ Y : Pitch/ Roll/ Yaw

※ Application : 1 HandHeld 2 Automotive 3 Drone 4 Marine 5 Timing

※ ODO : Odometer signal input

※  : Hot selling

## Dead Reckoning Modules

GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
----	------	----	----	----	-------	-----	-------------------	----------------	-------	-----------	-------------	---------------

**STMicro** (All electrical parts pass AEC-Q100)

ST-1612A-DGO (ADR)	●	●	●	●		○	1.8m (CEP) 0.5% (ADR)	○		ODO	②	16.0 x 12.2 x 2.4
ST-1612A-DGU (UDR)	●	●	●	●		○	1.8m (CEP) 5% (UDR)	○		UART	②	16.0 x 12.2 x 2.4
ST-1612A-DBO (ADR)	●	●	●		●	○	1.8m (CEP) 0.5% (ADR)	○		ODO	②	16.0 x 12.2 x 2.4
ST-1612A-DBU (UDR)	●	●	●		●	○	1.8m (CEP) 5% (UDR)	○		UART	②	16.0 x 12.2 x 2.4

## DR End Products

GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
----	------	----	----	----	-------	-----	-------------------	----------------	-------	-----------	-------------	---------------

**MTK**

G310 (ADR)	●	●	●	●		○	1.8m (CEP)	○		BT	① ②	96.0 x 63.0 x 14.7
B310 (ADR)	●	●	●		●	○	1.8m (CEP)	○		BT	① ②	96.0 x 63.0 x 14.7
 G310-U (UDR)	●	●	●	●		○	2.5m (CEP)	○		BT	① ②	96.0 x 63.0 x 14.7
B310-U (UDR)	●	●	●		●	○	2.5m (CEP)	○		BT	① ②	96.0 x 63.0 x 14.7

※ **ADR /UDR : Automotive Dead Reckoning/ Untethered Dead Reckoning**

※ **P/ R/ Y : Pitch/ Roll/ Yaw**

※ **Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing**

※ **ODO : Odometer signal input**

※  **: Hot selling**



**LOCOSYS**

GNSS Wireless & Communication



**Base station**

**Rover**



















**Rover**



























**Rover**

**Rover**

**Rover**

**RTK Solution**


RTK Modules		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
 RTK-1010								0.01m+1ppm < 1.5 m CEP (Autonomous)				UART	② ③ ④	10.1 x 9.7 x 2.2
RTK-1010-SB								0.01m+1ppm 2.5 m CEP (Autonomous)				UART	④	10.1 x 9.7 x 2.2
 RTK-1612								0.01m+1ppm < 1.5 m CEP (Autonomous)	< 0.2deg			UART	② ③ ④	16.0 x 12.2 x 2.4


RTK Embedded board		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
 RTK-4671-MH								0.01m+1ppm < 1.5 m CEP (Autonomous)				UART	② ③ ④	71.0 x 46.0 x 7.7
RTK-4671-MHDR								0.01m+1ppm < 1.5 m CEP (Autonomous)				UART	② ③ ④	71.0 x 46.0 x 7.7
 RTK-4671-MHPD								0.01m+1ppm < 1.5 m CEP (Autonomous)	< 0.2deg			UART	② ③ ④	71.0 x 46.0 x 7.7
 RTK-4057-MHPD								0.01m+1ppm < 1.5 m CEP (Autonomous)	< 0.2deg			UART	② ③ ⑤	57.0 x 40.0 x 1.0

※ P/ R/ Y : Pitch/ Roll/ Yaw

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

RTK USB Dongle		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-4P	●	●	●		●		0.01m+1ppm < 1.5 m CEP (Autonomous)				Type C	①	27.5(D) x 95.0(H)
	RTK-15D	●	●	●	●	●		0.01m+1ppm < 1.5 m CEP (Autonomous)				Type C	①	27.5 x 37.85 x 13

RTK Box ( 4G-LTE )		GP	QZSS	GA	GL	BD	IR	Position Accuracy	Heading Accuracy	Dead Reckoning	P/R/Y	Interface	Application	Dimension(mm)
	RTK-M100	●	●		●	●		0.01m+1ppm < 1.5 m CEP (Autonomous)					① ③	98.0 x 82.0 x 40.0
	RTK-M200	●	●		●	●		0.01m+1ppm < 1.5 m CEP (Autonomous)					① ③	98.0 x 82.0 x 40.0
	RTK-M300	●	●	●	●	●		0.01m+1ppm < 1.5 m CEP (Autonomous)					② ③ ④	185.0 x 125.0 x 45.0

※ P/R/Y : Pitch/ Roll/ Yaw

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

**LOCOSYS**

*GNSS Wireless & Communication*

***Timing Module***



***PCIe Card***



PCle Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>											
LS26030	●	●				○		3m (2D RMS)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-2RE	●	●					○	3m (2D RMS)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-B	●	●	●		●	○		2.5m (CEP)	USB	① ②	50.8 x 28.5 x 3.2
LS26030-G	●	●	●	●		○		2.5m (CEP)	USB	① ②	50.8 x 28.5 x 3.2

Mini PCle Card	GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Application	Dimension(mm)
<b>MTK</b>											
LS26031	●	●				○		3m (2D RMS)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-2RE	●	●					○	3m (2D RMS)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-B	●	●	●		●	○		2.5m (CEP)	USB	① ②	26.65 x 28.5 x 3.2
LS26031-G	●	●	●	●		○		2.5m (CEP)	USB	① ②	26.65 x 28.5 x 3.2



※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

## Timing module

GP	QZSS	GA	GL	BD	Flash	ROM	Position Accuracy	Interface	Timing Performance	Application	Dimension(mm)
----	------	----	----	----	-------	-----	-------------------	-----------	--------------------	-------------	---------------

### STMicro

ST-1612-T	●		●		○		2.5m (CEP)	UART/I <sup>2</sup> C USB/CAN Bus	5 ns	⑤	16.0 x 12.2 x 2.2
 ST-1612i-GT	●	●	●	●	○		1.8m (CEP)	UART	3.9 ns	⑤	16.0 x 12.2 x 2.4
 ST-1612i-GTs	●	●	●	●	○		1.8m (CEP)	USB	3.9 ns	⑤	16.0 x 12.2 x 2.4
ST-1612i-BT	●	●	●	●	○		1.8m (CEP)	UART	3.9 ns	⑤	16.0 x 12.2 x 2.4
ST-1612i-BTs	●	●	●	●	○		1.8m (CEP)	USB	3.9 ns	⑤	16.0 x 12.2 x 2.4

※ Application : ① HandHeld ② Automotive ③ Drone ④ Marine ⑤ Timing

※  : Hot selling

# LOCOSYS

20F.-13, No.79, Sec. 1, Xintai 5th Rd.  
Xizhi Dist., New Taipei City 22101  
Taiwan R.O.C.  
[www.locosystech.com](http://www.locosystech.com)

**Tel** : 886-2-8698-3698  
**Fax** : 886-2-8698-3699  
**Mail** : [info@locosystech.com](mailto:info@locosystech.com)

